

YHK®

Silent Chain

YHK Chain No.	Pitch	Chain Width	Pin diameter	Pin length	Distance from hole center to tooth	Plate depth	Plate thickness	Guide Form	Number or plates	Ultimate tensile strength	Average tensile strength	Weight per meter
	P	b mm	d2 max	b4 max	h1	h2 max	T/t max			Q min.	Qo	q
	mm	mm	mm	mm	mm	mm	mm	mm	n	KN	KN	Kg/m
CL04A 2x3	6.35	3.1	2.7 -2.52	6.2	3.92	6.72	1.03/0.8	Outside	5	5	5.5	0.173
CL04A 3x4	6.35	5.18	2.7 -2.52	8.4	3.92	6.72	1.03/0.8	Outside	7	7.6	8.2	0.248
CL04A 4x5	6.35	7.25	2.7 -2.52	11	3.92	6.72	1.03/0.8	Outside	9	9.5	10.5	0.34
CL04A 2x3	6.35	3.1	2.4	6.2	3.9	6.7	1.03/0.8	inside	5	5.2	5.5	0.169
CL04A 3x4	6.35	5.18	2.4	8.4	3.9	6.7	1.03/0.8	inside	7	7.8	8.2	0.242
CL04A 4x5	6.35	7.25	2.4	10.6	3.9	6.7	1.03/0.8	inside	9	10.4	10.5	0.315

