

Timing Chain

YHK Chain No.	Pitch	Transverse pitch	Width between inner plates	Roller diameter	Pin diameter	Pin length	Inner plate depth	Ultimate tensile strength	Average tensile strength	Weight per meter
	P	Pt Mon	b1 min	d1 max	d2 max	L max	h2 max	Q min.	Qo	q
	mm	mm	mm	mm	mm	mm	mm	KN	KN	Kg/m
*25	6.350		3.10	3.30	2.31	7.80	5.90	3.5	4.2	0.13
*25H	6.350		3.10	3.30	2.31	9.00	5.90	4.8	5.2	0.16
*25SH	6.350		3.10	3.30	2.01	9.00	5.90	5.2	5.5	0.17
5.00E-01	8.000		4.60	5.65	3.05	12.35	7.60	7.8	8.2	0.38
05H-1	8.000		4.60	5.65	3.05	11.40	7.60	7.8	8.2	0.38
*219HT	7.774		4.90	4.59	3.00	11.50	7.50	7.8	9.5	0.32
*BF05T	8.000		4.80	4.77	3.28	11.60	7.60	7.0	9.2	0.35
06BH	9.525		3.84	6.35	3.28	10.60	8.20	9.0	9.5	0.35
06BT-1	9.525		5.72	6.35	3.28	12.50	8.20	9.0	9.5	0.39
06BT-2	9.525	10.24	5.72	6.35	3.28	22.90	8.20	16.9	17.9	0.80
*C35-2	9.525	10.13	4.77	5.08	3.58	22.20	8.70	15.8	19.0	1.21
*35-1	9.525		4.77	5.08	3.58	12.15	8.95	7.9	9.8	0.33
*35-2	9.525	10.13	4.77	5.08	3.58	22.20	8.95	15.8	19.0	0.63
06B-1	9.525		5.72	6.35	3.28	13.20	8.20	8.9	10.0	0.41
06B-2	9.525	10.24	5.72	6.35	3.28	23.50	8.20	16.9	17.9	0.77
06BH	9.525		5.72	6.35	3.28	13.90	8.20	9.0	10.0	0.45

