



Super Professional

YHK CHAIN NO.	JAPAN CHAIN NO.	Pitch		Roller Dia.	Width between inner plates	Pin Dia	Pin Length		Plate Thickness		Weight		Tensile Strength		Seal Type	Connecting Link				
		mm	in				mm	mm	mm	mm	mm	mm	kgs	lbs		KN	Lbs	O/X	Rivet	Clip
415MX	415NZ	12.70	1/2	7.75	4.76	3.96	13.30	0.524	1.50	1.50	0.70	1.54	19.00	4269.87	/	/	*			
420MX	420NZ	12.70	1/2	7.77	6.25	3.96	15.70	0.619	1.80	1.80	0.81	1.79	21.00	4719.33	/	/	*			
428MX	428NZ (428M)	12.70	1/2	8.51	7.75	4.45	17.80	0.701	1.80	1.80	0.99	2.18	23.00	5168.79	/	/	*			
520MX	520NZ	15.875	5/8	10.16	6.35	5.24	18.60	0.733	2.20	2.20	1.76	3.88	38.00	8539.74	/	*	*			
525MX	525NZ	15.875	5/8	10.16	7.95	5.24	20.20	0.796	2.20	2.20	1.87	4.12	38.00	8539.74	/	*	*			
530MX	530NZ (50NZ)	15.875	5/8	10.16	9.40	5.24	21.60	0.851	2.20	2.20	1.98	4.37	38.00	8539.74	/	*	*			
630MX	630NZ	19.05	3/4	11.91	9.40	5.94	22.60	0.890	2.42	2.42	2.74	6.04	36.00	8090.77	/	*	*			

YHK Super are extra reinforced chains. With Solid Bushing & Through-hardened Roller, Super Chains perform with excellent response to wear and elongation. YHK Super Chains are suitable for standard as well as racing applications whenever O-Ring chain is not required.

*Outer Plate Color Available: Golden Finished; Silver Finished