

## ATV X-Ring

YHK CHAIN NO.	JAPAN CHAIN NO.	Pitch		Roller Dia.	Width between inner plates	Pin Dia	Pin Length		Plate Thickness		Weight		Tonelle Otroneth		Seal	Commonting Link	
									inner	outer 100L	100L	100L	Tensile Strength		Type	Connecting Link	
		mm	in	mm	mm	mm	mm	in	mm	mm	kgs	ibs	KN	Lbs	O/X	Rivet	Clip
X–RING																	
420UX	420VM	12.70	1/2	7.77	6.35	3.96	19.00	0.749	1.80	1.80	0.93	2.05	18.00	4045.14	X	*	*
428UX	428VM	12.70	1/2	8.51	7.94	4.45	21.20	0.835	2.03	2.03	1.23	2.71	22.00	4944.06	X	*	*
520UX	520VM	15.875	5/8	10.16	6.40	5.24	20.80	0.820	2.20	2.20	1.86	4.10	36.00	8090.28	X	*	*
525UX	525VM	15.875	5/8	10.16	7.95	5.24	22.30	0.879	2.20	2.20	1.96	4.32	36.00	8090.28	X	*	*
530UX	530VM	15.875	5/8	10.16	9.40	5.24	24.90	0.981	2.42	2.42	2.27	5.00	42.00	9438.66	X	*	*
630UX	630VM	19.05	3/4	11.91	9.40	5.94	28.60	1.127	3.25	3.25	2.91	6.42	49.00	11011.77	X	*	*



YHK X-Ring Chains are specially designed to be used on high powered as well as touring bikes. With a special 4-lips seal ring -X-Ring safely sealed lubrication inside the chain during its lifetime. With low frictional resistance, YHK X-Ring Chains operate much softer & cooler and, engaged beter than traditional O-Ring chains. Also X-Ring increased the lifetime of the chain considerably as well.

YHK ATV Chains use low friction & long lifetime X-Ring and, its performance are good for all quad types.

\*Outer Plate Color Available:Golden Finished; Silver Finished

\*Painted Color Plate Available:Red,Yellow,Orange,Green,Blue